# NW-LZY50A INTEGRAL REELECTIONOPERATING LAMP





# NW-LZY50A

### FEATURES AND HIGHLIGHTS

#### Technical parameters

• Illumination at 1m (Lux):160000• Brightness control range:20 levels adjustable• Color temperature (Kelvin):4500±250• Color rendering index (CRI):≥85• Temperature rise (Surgeon head)(°C):≤1• Temperature rise (surgical field)(°C):≤1• Total irradiance Ee (W/m2):≤1400• Radiant power Ee/Ec (mW/m2lux):≤4• Effective focusing depth (cm):60-120• Lighting spot size (cm):16-28• L1+L2 depth of illumination (cm):≥120• Bulb type:Halogen• Bulb power (w):150• Average bulb life (hours):≥1500• Average bulb life (hours):2• Bulb power (w):150• Average bulb life (hours):≥1500• Average bulb life (hours):≥1500	<ul> <li>Diameter of lighthead (mm):</li> </ul>	500
• Color temperature (Kelvin): $4500\pm250$ • Color rendering index (CRI): $\geq 85$ • Temperature rise (Surgeon head)(°C): $\leq 1$ • Temperature rise (surgical field)(°C): $\leq 1$ • Total irradiance Ee (W/m2): $\leq 1400$ • Radiant power Ee/Ec (mW/m2lux): $\leq 4$ • Effective focusing depth (cm): $60-120$ • Lighting spot size (cm): $16-28$ • L1+L2 depth of illumination (cm): $\geq 120$ • Bulb type:Halogen• Bulb power (w): $150$ • Average bulb life (hours): $\geq 1500$ • Bulb brand:OSRAM• Bulb brand:OSRAM• Bulb power (w): $150$ • Bulb power (w): $150$	<ul> <li>Illumination at 1m (Lux):</li> </ul>	160000
• Color rendering index (CRI):       ≥85         • Temperature rise (Surgeon head)(°C):       ≤1         • Temperature rise (surgical field)(°C):       ≤1         • Total irradiance Ee (W/m2):       ≤1400         • Radiant power Ee/Ec (mW/m2lux):       ≤4         • Effective focusing depth (cm):       60-120         • Lighting spot size (cm):       16-28         • L1+L2 depth of illumination (cm):       ≥120         • Bulb type:       Halogen         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb brand:       OSRAM         • Bulb brand:       0SRAM         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb power (w):       1500	Brightness control range:	20 levels adjustable
• Temperature rise (Surgeon head)(°C):≤1• Temperature rise (surgical field)(°C):≤1• Total irradiance Ee (W/m2):≤1400• Radiant power Ee/Ec (mW/m2lux):≤4• Effective focusing depth (cm):60-120• Lighting spot size (cm):16-28• L1+L2 depth of illumination (cm):≥120• Bulb type:Halogen• Bulb prand:OSRAM• Bulb power (w):150• Average bulb life (hours):≥1500• Bulb brand:OSRAM• Bulb power (w):150• Bulb power (w):150• Bulb power (w):150	Color temperature (Kelvin):	4500±250
• Temperature rise (surgical field)(°C):       ≤1         • Total irradiance Ee (W/m2):       ≤1400         • Radiant power Ee/Ec (mW/m2lux):       ≤4         • Effective focusing depth (cm):       60-120         • Lighting spot size (cm):       16-28         • L1+L2 depth of illumination (cm):       ≥120         • Bulb type:       Halogen         • Bulb brand:       OSRAM         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb power (w):       150         • Bulb power (w):       1500         • Bulb power (w):       1500         • Bulb power (w):       1500	Color rendering index (CRI):	≥85
• Total irradiance Ee (W/m2):≤1400• Radiant power Ee/Ec (mW/m2lux):≤4• Effective focusing depth (cm):60-120• Lighting spot size (cm):16-28• L1+L2 depth of illumination (cm):≥120• Bulb type:Halogen• Bulb brand:OSRAM• Bulb power (w):150• Average bulb life (hours):≥1500• Bulb brand:OSRAM• Bulb power (w):150• Bulb power (w):150	<ul> <li>Temperature rise (Surgeon head)(°C):</li> </ul>	≤1
• Radiant power Ee/Ec (mW/m2lux):       ≤4         • Effective focusing depth (cm):       60-120         • Lighting spot size (cm):       16-28         • L1+L2 depth of illumination (cm):       ≥120         • Bulb type:       Halogen         • Bulb brand:       OSRAM         • Bulb quantity:       2+2         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb power (w):       1500         • Bulb power (w):       1500	<ul> <li>Temperature rise (surgical field)(°C):</li> </ul>	≤1
<ul> <li>Effective focusing depth (cm): 60-120</li> <li>Lighting spot size (cm): 16-28</li> <li>L1+L2 depth of illumination (cm): ≥120</li> <li>Bulb type: Halogen</li> <li>Bulb brand: OSRAM</li> <li>Bulb quantity: 2+2</li> <li>Bulb power (w): 150</li> <li>Average bulb life (hours): ≥1500</li> <li>Bulb brand: OSRAM</li> <li>Bulb brand: 1500</li> <li>Bulb brand: 1500</li> <li>Bulb power (w): 150</li> </ul>	Total irradiance Ee (W/m2):	≤1400
Lighting spot size (cm):       16-28         L1+L2 depth of illumination (cm):       ≥120         Bulb type:       Halogen         Bulb brand:       OSRAM         Bulb quantity:       2+2         Bulb power (w):       150         Average bulb life (hours):       ≥1500         Bulb brand:       OSRAM         Bulb power (w):       1500         Bulb power (w):       1500         Bulb power (w):       1500         Bulb power (w):       1500	Radiant power Ee/Ec (mW/m2lux):	≪4
<ul> <li>L1+L2 depth of illumination (cm): ≥120</li> <li>Bulb type: Halogen</li> <li>Bulb brand: OSRAM</li> <li>Bulb quantity: 2+2</li> <li>Bulb power (w): 150</li> <li>Average bulb life (hours): ≥1500</li> <li>Bulb brand: OSRAM</li> <li>Bulb brand: OSRAM</li> <li>Bulb quantity: 2</li> <li>Bulb power (w): 150</li> </ul>	Effective focusing depth (cm):	60-120
• Bulb type:       Halogen         • Bulb brand:       OSRAM         • Bulb quantity:       2+2         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb power (w):       150         • Bulb brand:       OSRAM         • Bulb quantity:       2         • Bulb power (w):       150	Lighting spot size (cm):	16-28
• Bulb brand:       OSRAM         • Bulb quantity:       2+2         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb quantity:       2         • Bulb power (w):       150	L1+L2 depth of illumination (cm):	≥120
• Bulb quantity:       2+2         • Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb quantity:       2         • Bulb power (w):       150	Bulb type:	Halogen
• Bulb power (w):       150         • Average bulb life (hours):       ≥1500         • Bulb brand:       OSRAM         • Bulb quantity:       2         • Bulb power (w):       150	Bulb brand:	OSRAM
Average bulb life (hours): ≥1500     Bulb brand: OSRAM     Bulb quantity: 2     Bulb power (w): 150	Bulb quantity:	2+2
Bulb brand: OSRAM     Bulb quantity: 2     Bulb power (w): 150	Bulb power (w):	150
Bulb quantity: 2     Bulb power (w): 150	Average bulb life (hours):	≥1500
Bulb power (w): 150	Bulb brand:	OSRAM
	Bulb quantity:	2
Average bulb life (hours): ≥1500	Bulb power (w):	150
	Average bulb life (hours):	≥1500

#### Technical configuration

Rotating arm parts	1 set
☑ Balance arm	1 set
🗹 Main light	1 set
☑ Auxiliary light	1 set
🗹 Handle	1 pc



#### Material technology

The lampshade shell is made of high-quality aluminum alloy. The surface adopts the high-voltage electrostatic spraying process, and the imported environmentally friendly antibacterial plastic powder that used to ensures that the product meets the requirements of surgical hygiene. Also, this product has matte surface and no glint.




#### Bulb

It uses Osram imported lamp beads, the average service life is up to 1500 hours.



#### Color temperature&illumination

The color temperature is 4500±250K, the illuminance can reach 180,000 Lux, which can realize 20 levels adjustable. While satisfying high illuminance, the well-designed color temperature correction system provides a color temperature close to 4500K in natural daylight, ensuring that the surgeon can clearly and accurately identify the color of blood vessels and nerve bundles in the operation area.




#### Color rendering index

The color rendering index is as high as 85, which truly reflects the color of human tissues. It is suitable for various surgical scenes and greatly reduces the visual fatigue of medical staff due to long-term operations.



#### Temperature rise (surgical field)

Temperature rise (surgical field):≤1°C, this can avoid tissue drying due to high temperature and rapid blood clots at the wound, which will affect the operation.



#### Lens reflection system

The mirror surface applies special technology &oxidation &electrolysis new technology, which prolongs the life of more than 5 times than the coating reflection system, does not fade, and does not drop the oxide film. There are more than 5280 lenses, making the surgical field truly shadowless. The advanced color temperature compensation technology provides a color temperature that is closer to natural daylight and evenly covers the entire surgical area, ensuring that the surgeon can clearly and accurately identify the color of blood vessels and nerve bundles in the surgical area.



#### Lamp arm structure

The spring arm suspension system has six groups of universal directions and the 360° joint linkage is designed in an all-round way. It is completely positioned accurately and completely solves the drift.

#### Standby light source system

Assuming that the main lamp has a light source failure during the operation, the system will automatically switch the standby bulb mode within 0.2 seconds, the light intensity and the operation area will not be affected at all, ensuring the normal operation of the operation. The panel has a main light failure indicator to remind you to replace the bulb in time after the operation.

#### Back up battery

Optional back up battery can keep the operating lamp working for 3-4 hours in case of power failure to deal with various special situations.





#### Remote control

Infrared remote control makes the operation more convenient.





### NUMBER WIN



+86 18021231901

♥ No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@number-win.com

() www.number-win.com





As the circumstance of printing, the photos might have minor difference on color, tactile from real products. As the update of design and improvement, parameters and outlook of products might change, thanks for understanding.