NW207

TWO FUNCTIONS MANUAL BED





NW207

FEATURES AND HIGHLIGHTS





Technical parameters

| External size (LxWxH) | 2245x1000x510 mm |
|--|------------------|
| Mattress platform | 1925x830 mm |
| Safe working load | 250 kg |
| Back-rest adjustment | 0-75° (±10°) |
| Knee-rest adjustment | 0-35° (±10°) |



| ✓ Manual Cranks | 2pcs |
|---|------|
| ☑ 5" Hardshell Castors | 4pcs |
| ☑ Foldable Side Rail with ProErgo-Handle™ | 1set |
| ☑ ABS Grace Bed Ends with Safe Lock | 1set |
| ☑ IV Pole | 1set |
| ✓ IV Pole Prevision | 4pcs |
| ☑ Drainage Hook | 2pcs |
| ☑ Shoes Holder | 1set |
| | |





Optional

☐ Monkey Pole
☐ Balkan Traction Frame
☐ Directional Wheel





Desigr

Extra long and height head foot board, with curve surrounded design, provide conforting feeling for patients.



Plastic

Environmental plastic can be sterilized in 100°C, tensile upto 30MPa Virgin ABS material.



Steels | Painting

Baosteel from Fortune Global 500 11 Process epoxy painting, ASTM testing anti-baterial, paint thickness 0.12 mm, brightness 60°, paint can resist 50 kg impact.



Welding | Chassis


Panasonic robotic ensure, 360° full smooth wedlding Solid bed base made of 5.0 mm stamped rotating plate.



Hand Control


Retractable hand crank, 100,000 times remaining intact

Extreme protection device, sounds when tipped to the max position, Strong pallets to increase the bed height adjustment.



Platform

Stamping forming platform, smooth surface no welding scar, bearing 250KG load. Option resin X-ray translucent platform.



Guardrail

L-shaped foldable guardrail (Patent) with ProErgo-Handle™,patented parts. with red and green mark to indicated if the siderail is locked or not.Bended tube, solid installing, 0 shaking, anti-pinch, protect patient's safety.



Head & Foot Board

Head and foot board can be reversable, extra height design, size: 1000*563mm;

ABS Grace Bed Ends with Safe Lock, automatic lock without any manual operation on lock, on/off removable mark on hook lock.



Castors

5" hardshell casters

TPR tire no worn out after running 30KM, save anti-winding hard shell, united forming without bolts.

Pass Dynamic test: Bearing 120kg run 30KM and pass obstacles 500 time.



Drainage Hooks

Mobile plastic drainage hooks.



IV pole

Stainless Steel Column with plastic hook.



Shoes Holder

Shoes holder: 800*400mm, adjustable



NUMBER WIN



+86 18021231901

- No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
- export@number-win.com
- www.number-win.com















