NW307

THREE FUNCTIONS MANUAL BED





NW307







FEATURES AND HIGHLIGHTS

Technical parameters

External size (LxWxH)	2245x1000x435-745 mm
 Mattress platform 	1925x830 mm
 Safe working load 	250 kg
 Back-rest adjustment 	0-75° (±10°)
 Knee-rest adjustment 	0-35° (±10°)



Technical configuration

✓ Manual Cranks	3pcs
☑ 5" Hardshell Castors	4pcs
☑ Foldable Side Rail with ProErgo-Handle™	1set
☑ ABS Grace Bed Ends with Safe Lock	1set
☑ IV Pole	1set
✓ IV Pole Prevision	4pcs
☑ Drainage Hook	2pcs



Optional

- ☐ Monkey Pole
 ☐ Balkan Traction Frame
- ☐ Directional Wheel





Design

Extra long and height head foot board, with curve surrounded design, provide conforting feeling for patients



Plastic

Environmental plastic can be sterilized in 100°C, tensile upto 30MPa Virgin ABS material.



Steels | Painting

Baosteel from Fortune Global 500 11 Process epoxy painting, ASTM testing anti-baterial, paint thickness 0.12 mm, brightness 60°, paint can resist 50 kg impact.



Welding | Chassis


Panasonic robotic ensure, 360° full smooth wedlding Solid bed base made of 5.0 mm stamped rotating plate.



Hand Control

Retractable hand crank, 100,000 times remaining intact

Extreme protection device, sounds when tipped to the max position, Strong pallets to increase the bed height adjustment (435-745mm).



Platform

Stamping forming platform, smooth surface no welding scar, bearing 250KG load. Option resin X-ray translucent platform.



Guardrail

L-shaped foldable guardrail (Patent) with ProErgo-Handle™,patented parts. with red and green mark to indicated if the siderail is locked or not.Bended tube, solid installing, 0 shaking, anti-pinch, protect patient's safety.



Head & Foot Board

Head and foot board can be reversable, extra height design, size: 1000*563mm;

ABS Grace Bed Ends with Safe Lock, automatic lock without any manual operation on lock, on/off removable mark on hook lock.



Castors

5" hardshell casters

TPR tire no worn out after running 30KM, save anti-winding hard shell, united forming without holts

Pass Dynamic test: Bearing 120kg run 30KM and pass obstacles 500 time.



Drainage Hooks

Mobile plastic drainage hooks.



IV pole

Stainless Steel Column with plastic hook.



NUMBER WIN



+86 18021231901

- No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
- export@number-win.com
- www.number-win.com















