NW403 MANUAL BED





NW403











FEATURES AND HIGHLIGHTS

Technical parameters

Size (LxW)	2180x960 mm
Bed height adjustment	460-710 mm
 Mattress platform 	1925x830 mm
Safe working load	250 kg
 Back-rest adjustment 	0-75°(±10°)
 Knee-rest adjustment 	0-35°(±10°)
Reverse trendelenburg	0-12°
Trendelenburg	0-12°

Technical configuration


☑ Manual crank	4 pcs
☑ 5" hardshell castors with break	4 pcs
☑ Foldable side rail with ProErgo-Handle™	1 set
☑ ABS bed ends with safe lock	1 set
☑ IV pole	1 set
☑ IV pole prevision	4 pcs
☑ Drainage hook	2 pcs











Design

Use new and strong inserted ABS fire-proof panel avoid off.

Easy to be cleaned and installed.



Hand Crank

Retractable hand crank, 100,000 times remaining intact

Extreme protection device, sounds when tipped to the max position.



Bed Surface

Stamping forming platform, smooth surface no welding scar, bearing 250KG load. Option ABS platform and resin X-ray translucent platform.



Steels | Painting

Baosteel from Fortune Global 500. 11 Process epoxy painting, ASTM testing antibaterial, paint thickness 0.12mm, brightness 60°, paint can resist 50kg impact.



Wheels

TPR tire no worn out after running 30KM, save anti-winding hard shell, united forming without bolts.

Pass Dynamic test: bearing 120kg run 30KM and pass obstacles 500 times



Side Rail

L-shaped foldable guardrail(Patent), bended tube, solid installing, 0 shaking, anti-pinch, ensure patient's safety.



Welding | Chassis

Panasonic robotic ensure, 360° full smooth wedlding Solid bed base made of 5.0 mm stamped rotating plate.



Head & Foot Board

Full ABS material, head and foot board can be reversable.



IV Pole

Stainless steel solumn with plastic hook.



NUMBER WIN



+86 18021231901

- No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
- export@number-win.com
- www.number-win.com















