MWB041


OPERATION CONNECTING TROLLEY





NWB041

FEATURES AND HIGHLIGHTS



MAIN TECHNICAL PARAMETERS

Size	3650*640*(640-970)mm
Back-rest	0-75°(±10°)



☑ Crank System	2PC
☑ Back Rest Air Spring	IPC
☑ ABS Side Rail	1set
☑ Directional Wheel	2рс
☑ 6" Castors with Central Locking	4pcs
✓ IV Previsions	2pc
☑ IV Pole	1set
☑ Central Locking Break Pedal	4pcs
☑ Directional Wheel Release Pedal	4pcs











protect

cover all metal srews with rubber cap, protect screws form possible corrosion



Center Wheel

Can be engaged to facilitate direction control, enabling users to navigate the stretcher easily in hectic and dynamic environments.



connect with operating room

Transfer patient to operation room, prevent cross infection



Metal Material

Baosteel from Fortune Global 500 Panasonic Robotic ensure 360° full smooth wedlding



Plastic

Environmental plastic can be sterilized in 100°C, tensile upto 30MPa



Steels | painting

11 Process epoxy painting, ASTM testing antibaterial, paint thickness 0.12mm, brightness 60°, paint can resist 50kg impact



Metal Dust Cove

We use metal dust protection for crank system, more endurable than plastic cover



Bearing

We use robust tube in weight bearing structure



Autolock

The patient strecher will be auotlocked, when it slid to one side of the trolley



NUMBER WIN



+86 18021239272

No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@number-win.com

www.number-win.com















