NWD802 ELECTRIC BED





NWD802



FEATURES AND HIGHLIGHTS

Technical parameters

External size (LxW)	2150x980(±10mm)
Height adjustment	430-640mm(±10mm)
Mattress platform	1950x900mm
 Back-rest adjustment 	0-75° (±10°)
Knee-rest adjustment	0-45° (±10°)
Reverse trendelenburg	0-10° (±2°)
Trendelenburg	0-10° (±2°)
 Safe working load 	200 kg
 Voltage 100-230 V 	
 Frequency 50/60 Hz 	

Technical configuration

🗹 Linear motor	4pcs
☑ 5" double side castors, central locking	4pcs
🗹 ABS side rail extra height	1set
\blacksquare ABS bed ends with safe lock	1set
🗹 Hand controller	1pc
☑ IV pole prevision	4pcs
🗹 Drainage hook	2pcs
🗹 Central locking pedal	2pcs




Design

The simple and elegant head and foot board design of the bed meets the hospital's infection control requirements and supports daily disinfection operations.



Plastic

Environmentally friendly plastic, non-toxic and odorless



Painting

The overall bed body adopts a series of processes of pickling, phosphating, water washing and oxidation, and a fully automatic water spraying line uses powder electrostatic spraying process to achieve bright color and firm adhesion.



Weldingl Aluminum alloy side rail, 6-staff, collapsed type with safe lock.



Electric Control System Famous brand motor has passed UL medical certification, stable performance, and motor noise of 50dB.



Hand Controller

The hand controller has a flexible spring wire, which makes it convenient and flexible to operate the hospital bed in the best position. Nurses can easily control all standard functions, including one-button CPR and background light function.



Platform

The bed width is 900mm, using a four-piece bed board, made of high-quality cold-rolled steel plate stamped at one time, with a thickness of 1.0mm, and a multi-hole design for easy ventilation and anti-slip function. There are no solder joints on the surface, and there are steel pipe reinforcements on the back. It adopts a double-support unloading structure to extend the life of the hospital bed and has a load-bearing capacity of 200KG.



Siderail

C-type guardrail, with angle display function, made of PP engineering plastic, beautiful appearance, easy to operate, sturdy and durable, easy to clean, anti-pinch design, the guardrail lift uses a damper device to control speed and noise, and can be hidden under the bed panel when lowered flush with bed frame



Head & Foot Board

Simple and elegant bed head and foot shape, easy to disassemble and install, with medical record card at the foot of the bed



Castor

The four wheels use 125mm luxurious silent center control wheels, a highly stable stainless steel linkage system, and the braking is stable, flexible and convenient. The two-wheel design increases the landing area and stability.



Drainage Hook There are drainage hooks on both sides of the bed.





NUMBER WIN



+86 18021239272

♥ No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@number-win.com

() www.number-win.com





As the circumstance of printing, the photos might have minor difference on color, tactile from real products. As the update of design and improvement, parameters and outlook of products might change, thanks for understanding.

General catalogue