NWE302

PATIENT LIFT





NWE302

FEATURES AND HIGHLIGHTS

Technical parameters

| ■ Over size(L×W×H) | 58×70×93-113cm |
|---|----------------|
| Lifting height range | 200mm±20mm |
| Sitting Height | 45-65cm |
| Sitting surface size | 37×42cm |
| Passing width | ≥58cm |
| Maximum load capacity | 120kg |
| Package size(L×W×H) | 63×89×80cm |
| • G.W. | 35kg |

Technical configuration

| ☑ Bedpan | 1 pc |
|----------------|-------|
| ✓ Foam cushion | 1 pc |
| ☑ Seat belt | 1 set |



Design

Ergonomic, for multiple purposes, easy to move.



Material

The round tube is made of 2.0mm thick steel tube with paint surface, easy to clean, corrosion-resistant, strong load-bearing and anti-rust. The square tube is made of spraying carbon steel, high load-bearing capacity, waterproof and rust-proof.

Adopt manual welding, electroplating process, rust-proof and easy to clean.



Hydraulic pump

Stainless steel hydraulic pump, with height adjustment, lifting telescopic rod, solid steel rod, easy to adjust the height, solid and durable. Lifting speed 3-9mm/s.



Backrest

Blow molded backrest, soft and comfortable. With stable double safety belt buckle. Grip integrated in the back-rest, which is convenient for patients to grasp.



Cushion

High-density foam cushion, removable and easy to clean.



Armrest

Helping users to grip and lift more convenient. Foldable, convenient for patients to move.



Foot pedal

Anti-slip fixed foot pedal, providing a sense of safety for patients



Seat surface

Enlarged ABS seating surface, more stable, the maximum load bearing can be up to 120kg. With 180 °open angle, mobile and flexible, easy to operate. With mechanical lock, more secure.



Castor

Front 5" directional wheels with brakes Rear universal wheels. Flexible steering, smooth pushing and pulling.



Bedpan

Equipped with a disassemble bedpan, easy to use and clean.





NUMBER WIN



+86 18021239272

No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@number-win.com

www.number-win.com















