NWF299-5

ELECTRIC OBSTETRIC BED





NWF299-5

FEATURES AND HIGHLIGHTS









Technical parameters

External (LxW):	1950x660mm
Table height:	680-940mm
Seat plate up folding:	0-20°
Seat plate down folding:	0-9°
Back plate up folding:	0-45°
Back plate down folding:	0-10°
 Leg plate abduction: 	0-90°
Load bearing:	≤300kg



Technical configuration

✓ Arm support	2 pcs
✓ Handle	2 pcs
✓ Leg support	2 pcs
✓ Stirrup	2 pcs
☑ Slider	4 pcs
✓ Tightener	2 pcs
✓ Hand controller	1 pc
✓ Foot switch	1 pc
☑ Stainless steel basin	1 pc










Material

The chassis cover is made of high quality 304 stainless steel, which is welded by the robot seamlessly. The shape is beautiful and stable.



Mattress

Polyurethane foam mattress, waterproof and seamless, easy cleaning and disinfection.



Foot pedal controller

All the functions are controlled by hand controller and foot switch.



Braking system

The pedal controls the brake function of the casters.



Control System

Electric control the height lifting, seat plate up and down, back plate up and down, convenient operations.



Arm Support

The arm support could be adjusted into multiple angles with the straps, it can be used to comfortably fix the puerpera's arm at various angles.



Leg supports

The leg support is integrated with stirrup function, and the delivery bed is equipped with a pair of stirrups.



Auxiliary Table
The auxiliary table can be folded 90° outwards, used as a instrument table, detachable, and adapt to a variety of surgical environments.



Pull handles

Pull handles can be folded to horizontal position. Easy patient mobilisation.



Sewage basinEquipped with stainless steel sewage basin and other various accessories.



NUMBER WIN



+86 18021239272

- No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
- export@number-win.com
- www.number-win.com















