NWM038-4 PATIENT TROLLEY






NWM038-4

FEATURES AND HIGHLIGHTS



Size	1960*700*(620-880)mm
 Back-rest 	0-75°
 Height Adjustment 	620-880mm





Technical configuration

1set
1pc
4pcs
2pcs
1set
1pc
1pc
1pc







steels | Painting Baosteel from Fortune Global 500 11 Process epoxy painting, ASTM testing antibaterial, paint thickness 0.12mm, brightness 60°, paint can resist 50kg impact



welding | chassis

Panasonic Robotic ensure, 360° full smooth welding Solid bed base made of 5.0mm stamped rotating plate

Patent angle indicator



bumper straps

The trolley frame with the bumper straps could reduce the impact force



Trolley surface

The trolley surface is made of powder coated steel, smooth surface no welding scar




Steel hanging crank, 100,000 times remaining intact, it can be fold under the bed when not in use



5 inch

TPR tire no worn out after running 30KM, save anti-winding hard shell, united forming without bolts

Pass Dynamic test: Bearing 120kg run 30KM and pass obstacles 500time



Aluminum alloy side rail, 6-staff,collapsed type with safe lock



6cm thickness flame retardant high-density foam with U leather cover



Oxygen cylinder rack - adjustable for anysize tank



NUMBER WIN



+86 18021239272

♥ No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@number-win.com

() www.number-win.com





As the circumstance of printing, the photos might have minor difference on color, tactile from real products. As the update of design and improvement, parameters and outlook of products might change, thanks for understanding.

General catalogue