NWZ-BD23

ELECTRIC EXAMINATION TABLE





NWZ-BD23

Back plate adjustment Height adjustment

FEATURES AND HIGHLIGHTS

Technical parameters

External L*W*H	1810*680* (570-860) mm
Back-rest Adjustment	0-75°

Technical configuration

✓ Pillow	1pc
☑ Motor	1pc
☑ Mechanical Lever to Adjust Back Rest	1pc
✓ Casters	4Pcs
☑ Hand Controller	1pc
☑ Paper Roll Holder	1pc



Eletronics

 Voltage 	100-240V
Frequency	50/60Hz
Plug	as required (hospital grade)





leather

Flame retardant, yellow resistance, mildew resistance, bending resistance, 100,000 times wear resistance



Sponge

Flame retardant, 4 cm thickness, high-density foam, density 30 kg/m³



Painting

11 Process epoxy painting, ASTM testing antibaterial, paint thickness 0.12mm, brightness 60°, paint can resist 50kg impact



Metal Material
Baosteel from Fortune Global 500
Panasonic Robotic ensure 360° full smooth wedlding




Electric SYSTEMTaiwan motor, Noise under 50dB, with lifetime 20,000times moveme



Back adjustBack adjust can choose rachet or motor



1.2-1.5 mm Thickness powder coated steel frame, 150 kg bear loading



2 pcs 2' Hidden castors, 2 pcs 2' universal wheels



Hand controller, keep qualified after 2000 times use



Engineering ABS material plug, foot pad



Paper roll holder Foot bar system Motor to adjust the back sectio



NUMBER WIN



+86 18021239272

No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@number-win.com

www.number-win.com















